

Palletworx

Material:

-HDPE [High density polyethylene]

Features:

- F.D.A. /U.S.D.A / M.A.F. Approved material [Food Grade]
- Will not splinter, damage goods or injure handling personnel
- Weather resistant [won't rot or become subject to fungal growth]
- Freezer friendly [operating parameters, -40° to 65° Celsius]
- Resistant to common industrial chemicals [acids, alkalis, oil +]

Function:

- Nest-able within each other [saves space when unused or in transit. 25 pallets per meter stack versus 6 wooden or injection moulded]
- Recyclable
- Lightweight* [4.8kg] @ 4mm material
- *Pallet weights vary depending on strength required

Specification:


- 2 sizes available 1160 x 1160 x 128mm & 1120 x 1120 x 128mm
- 3 gauges 3mm, 4mm, 5mm
- 4 way entry



Palletworx
PO Box 37 022
Stokes Valley
Lower Hutt
New Zealand
Tel: +64 4 563 7879
Fax: +64 4 563 7877
Email: john@palletworx.com

1160/1120 export pallet

lightweight - hygienic - energy efficient - cost effective export solutions
SPECIALISTS IN PLASTIC PALLETS AND LAYERING SYSTEMS



Palletworx



Palletworx
PO Box 37 022
Stokes Valley
Lower Hutt
New Zealand
Tel: +64 4 563 7879
Fax: +64 4 563 7877
Email: john@palletworx.com

1160/1120 export pallet

lightweight - hygenic - energy efficient - cost effective export solutions

SPECIALISTS IN PLASTIC PALLETS AND LAYERING SYSTEMS